

Pioneer

BDP-V6000 PROFESSIONAL BLU-RAY DISC PLAYER

FEATURES BONUS VIEW & BD LIVE



OVERVIEW

THE BDP-V6000 IS THE NEW PROFESSIONAL BLU-RAY DISC PLAYER FROM PIONEER. IT SUPPORTS HIGH-DEFINITION BLU-RAY DISC AND STANDARD DEFINITION DVD MEDIA PLAYBACK IN BOTH NTSC AND PAL FORMATS TO PROVIDE FLEXIBLE, RELIABLE PLAYBACK OF DOMESTIC AND INTERNATIONAL CUSTOMER CONTENT IN DEMANDING APPLICATIONS. THIS BLU-RAY DISC PLAYER IS IDEAL FOR MULTIPLE APPLICATIONS AND VENUES THAT REQUIRE HIGH-DEFINITION PLAYBACK, SUCH AS DIGITAL SIGNAGE, MUSEUMS, VIDEO WALLS, HOUSES OF WORSHIP, PUBLIC DISPLAYS, AND BROADCAST.

FEATURES

- **SERIAL RS-232C SUPPORT:** ALLOWS INTEGRATORS TO CONTROL PLAYER THROUGH ANY NUMBER OF EXTERNAL DEVICES
- **ENHANCED SEARCH OPTIONS:** USERS CAN SEARCH DIRECTLY WITHIN THE DISC'S VIDEO CONTENT TO A TITLE, CHAPTER, OR TIME CODE QUICKLY AND EASILY
- **PLAYS 30, 25, AND 24 FRAMES PER SECOND (FPS):** SUPPORTS PLAYBACK OF ALL BD TITLES THAT DO NOT CONTAIN REGION CODES FROM OUTSIDE THE PLAYER'S "HOME" REGION
- **PROFESSIONAL GRAPHIC USER INTERFACE (GUI):** A NEWLY DESIGNED GUI PROVIDES IMPROVED PLAYER SET-UP AND INTERNAL PLAYLIST OPERATION
- **BONUS VIEW & BD-LIVE CAPABILITY**
- **RACK MOUNT KIT INCLUDED**

SPECIFICATIONS FOR PIONEER BDP-V6000 PROFESSIONAL BLU-RAY DISC PLAYER

Model	BDP-V6000		
Type	Blu-ray Disc PLAYER		
Rated Voltage	AC 120 V		
Rated Frequency	60 Hz		
Power Consumption	32 W		
Power Consumption (Standby)	0.3 W		
Inrush Current	26 A or less		
Weight	7 lb. 12 oz. (3.5 kg)		
External Dimensions (including projecting parts)	16 9/16 in. (W) x 3 in. (H) x 11 5/16 in. (D) 420 mm (W) x 75 mm (H) x 287 mm (D)		
Tolerable Operating Temperature	+41°F to +95°F (+5°C to +35°C)		
Tolerable Operating Humidity	5% to 85% (no condensation)		
Output Terminals	HDMI	1 set, 19-pin: 5 V, 250 mA	
	Video Outputs	Video	1 set, RCA jack: 1.0 Vp-p (75 Ω)
		Component Video	1 set: RCA jacks: Y: 1.0 Vp-p (75 Ω) PB, PR: 0.7 Vp-p (75 Ω)
	Audio Outputs	7.1-channel (multi-channel: front left/right, surround left/right, center, surround back left/right, subwoofer)	1 set, Number of channels: 8, RCA jacks
		Audio Output Level	200 mVrms (1 kHz, -20dB)
		Frequency Response	4 Hz to 88 kHz (192 kHz sampling)
	Digital Audio Outputs	Optical	1 set, Optical digital jack
LAN	1 set, Ethernet jack (100BASE-TX)		
Control	Input	1 set, Minijack (3.5 Ø)	
USB	1 set, Type A		
RS-232C	1 set, D-sub 9-pin (male) connector conforming to RS-232C standards x 1 (inch screw threads)		



REAR VIEW OF BDP-V6000